

# SUPERLOCK LATCH DEADLOCK



SPECIFICATION SHEET / 190

- Easy to fit - Slim 70mm wide stainless steel lock case along with adjustable and removable bolts ensure easy fitting to gates.
- Latchbolt is adjustable in length for precise fitting on site. Easy to rotate for Left and Right handed gates.
- Supplied with handles - two styles available.
- Supplied with bolt support plate and gate post strike plate.



## PRODUCT DETAILS

Product code:	Description:
BLD1030	To fit flat bar and up to 30mm box section
BLD4060	To fit 40 to 60mm box section

Style of handle:	Description:
T	Traditional handle set
S	Black lever handle set

**Bolts:** Adjustable, latchbolt springs 15mm and deadbolt moves to 30mm.

Perfect for both LH/RH gates.



## INSTALLATION

- Drill 2 x 9mm holes at 140mm centres for fixing bolts provided.
- Drill a second 18mm clearance hole for the latchbolt at 60mm centres up from the bottom fixing hole.
- Hold the lock against the back of the box section and screw the latchbolt through the bottom 18mm hole.
- Lock the latchbolt and deadbolt with the hex key supplied by inserting the hex key into the end of the latchbolt and the deadbolt.
- Fix lock in place using the stainless steel bolt support plate and the countersunk screws provided. Ensure the latchbolt and deadbolt move freely.
- Fix strike plate by either welding or screw fixing onto the gate post
- MAINTENANCE** Every 6 months, lubricate the latchbolt and deadbolt with light oil. Annually, dismantle the lock and spray mechanism with light oil.

 **GATEMASTER**

VISIT [SIGNETLOCKS.CO.UK](http://SIGNETLOCKS.CO.UK) FOR MORE INFORMATION

